




Coating (standard):



Dimensions

Material index	d [mm]	L [mm]	D [mm]	k [mm]	Lg [mm]	Recesses	Type of coating
3111100300TXAL2T	10.0	300	25.0	4.2	80	TX 40	A (Yellow zinc coating)
3111080080TXAL2T	8.0	80	22.0	3.6	40	TX 40	A (Yellow zinc coating)
3111080380TXAL2T	8.0	380	22.0	3.6	80	TX 40	A (Yellow zinc coating)
3111060100TXAL2T	6.0	100	16.0	2.8	40	TX 30	A (Yellow zinc coating)
3111100360TXAL2T	10.0	360	25.0	4.2	80	TX 40	A (Yellow zinc coating)
3111100340TXAL2T	10.0	340	25.0	4.2	80	TX 40	A (Yellow zinc coating)
3111080280TXAL2T	8.0	280	22.0	3.6	80	TX 40	A (Yellow zinc coating)
3111060140TXAL2T	6.0	140	16.0	2.8	70	TX 30	A (Yellow zinc coating)
3111100160TXAL2T	10.0	160	25.0	4.2	80	TX 40	A (Yellow zinc coating)
3111060240TXAL2T	6.0	240	16.0	2.8	70	TX 30	A (Yellow zinc coating)
3111080320TXAL2T	8.0	320	22.0	3.6	80	TX 40	A (Yellow zinc coating)
3111100380TXAL2T	10.0	380	25.0	4.2	80	TX 40	A (Yellow zinc coating)
3111080360TXAL2T	8.0	360	22.0	3.6	80	TX 40	A (Yellow zinc coating)
3111060220TXAL2T	6.0	220	16.0	2.8	70	TX 30	A (Yellow zinc coating)
3111080400TXAL2T	8.0	400	22.0	3.6	80	TX 40	A (Yellow zinc coating)
3111100240TXAL2T	10.0	240	25.0	4.2	80	TX 40	A (Yellow zinc coating)
3111080200TXAL2T	8.0	200	22.0	3.6	80	TX 40	A (Yellow zinc coating)
3111080180TXAL2T	8.0	180	22.0	3.6	80	TX 40	A (Yellow zinc coating)
3111100400TXAL2T	10.0	400	25.0	4.2	80	TX 40	A (Yellow zinc coating)
3111080240TXAL2T	8.0	240	22.0	3.6	80	TX 40	A (Yellow zinc coating)

[illegible]